

PŘEDSTAVUJEME

EPCOS, TOOLOVA, WÜRTH, STOCKO, PANASONIC
SPECTRUM CONTORL



ELEKTRONICKÉ SOUČÁSTKY
Luženice 10, 344 01 Domažlice
tel.: 379 723 915, fax: 379 725 868

info@atd-elektronik.cz www.atd-elektronik.cz



CITEL NABÍZÍ:

- POJISTKY -

 BA	2 electrode miniature gas discharge tube	Diameter 5 mm (BA) Opt. with termination (BAS) Spark over voltage from 90 up to 350 V. Nominal discharge current : 2,5 kA/ 10 times
 BB	2 electrode gas discharge tube	Diameter 8 mm (BB), Opt. with termination (BBS) Spark over voltage from 90 up to 500 V. Nominal discharge current : 5 kA /10 times
 BH	2 electrode gas discharge tube	Diameter 8 mm (BH) Opt. with termination (BHS) Spark over voltage from 600 up to 3500 V Nominal discharge current : 2,5 kA/ 10 times
 P100	Heavy duty gas discharge tube	- without connection (P100N) - avec cosses (P100) - with cables (P100S) - available for spark over voltage from 350 up to 500V - Nominal discharge current 150 kA onde (8/20µs)
 CA8B	2 electrode gas discharge tube	Spark over voltage from 230 a 540 V Nominal discharge current : 10 kA /10 times
 CA5R	2 electrode glass-metal gas discharge tube	Spark over voltage from de 230 a 250 V Nominal discharge current : 2,5 kA onde (8/20µs) : 10 times
 BM	3 electrode miniature gas discharge tube	Diameter 5 mm Version court-circuit possible (BMC) Opt. with termination (BMS) Version montage en surface (BM-CMS) Spark over voltage from 90 up to 250 V Nominal discharge current : 5 kA/10 chocs
 BT	3 electrode gas discharge tube	Diameter 8 mm Version court-circuit possible (BTC/BTRC) Opt. with termination (BTS/BTR) Spark over voltage from 90 up to 500 V Nominal discharge current : 10 kA /10 chocs

Podrobnější informace na:
info@atd-elektronik.cz